

SIMPLE YET POWERFUL

VANQUISH[®]

60 SERIES

- **Fully Waterproof**
IP68-rated, waterproof up to 5 m (16 ft)
- **Multi-IQ[®] Technology**
Proven simultaneous multi-frequency technology
- **Rechargeable Battery**
10-hour runtime with rechargeable lithium-ion battery
- **Smart Discrimination**
30 discrimination segments, 119 Target IDs and Iron Bias control
(3 levels on 460) (4 levels on 560)
- **Lighter Swing**
360 and 460 Weight: 1.16 kg (2.6 lbs)
560 Weight: 1.26 kg (2.8 lbs)
- **Low-Light Vision**
Red LED display and control pod flashlight (460/560)
- **Advanced Target Feedback**
Low-latency Bluetooth LE[®] Audio and handgrip vibration (460/560)
- **Clear Tone Response**
Five target tones with ferrous volume control (560)

POWERED BY **Multi-IQ[®]**
Simultaneous Multi-Frequency Technology





Technical Specifications

VANQUISH 360 **VANQUISH 460** **VANQUISH 560**

| | | | |
|--|--|--|----------------------------------|
| Search Mode | Park, Beach, All-Metal | Park, Field, Beach, User Profile | Park, Field, Beach, User Profile |
| All-Metal Shortcut | No | | Yes |
| Custom User Search Profile | No | | Yes |
| Operating Frequencies (kHz) | Multi-IQ® | | |
| Noise Cancel | Auto (19 Channels) | | |
| Bluetooth Audio | No | | Yes |
| Iron Bias | Fixed | 3 Levels | 4 Levels |
| Sensitivity Control | 5 Levels | | 10 Levels |
| Volume Control | 5 Levels | | 10 Levels |
| Iron Volume Control | Fixed | | 10 Levels |
| Accept Reject | No | | Per Segment |
| Target Tones | 3 Tones (Low, Mid, High) | | 5 Tones |
| Discrimination Segments | 6 Segments | | 30 Segments |
| Discrimination Notch | No | | Yes |
| Pinpoint Mode | Yes | | |
| Targets IDs | -19 to 119 | | |
| Depth Gauge | 5 Levels | | |
| Length | Extended: 142 cm (56 in) / Collapsed: 79.5 cm (31.2 in) | | |
| Weight (incl. batteries) | 1.16 kg (2.6 lbs) | | 1.26 kg (2.8 lbs) |
| Display | Monochrome LCD | Monochrome LCD with Red LED Backlight | |
| Backlight | No | Off/Low/High | |
| Flashlight | No | On/Off | |
| Vibration | No | On/Off | |
| Supplied Coil | V10X 10" x 7" Double-D Coil | | V12X 12" x 9" Double-D Coil |
| Audio Output | In-Built Loudspeaker Wired 3.5 mm (1/8") Headphones | In-Built Loudspeaker Wired 3.5 mm (1/8") Headphones Bluetooth® LE Wireless Audio | |
| Supplied Headphones | No | Wired Headphones | |
| Supplied Batteries | Internal Lithium-Ion Rechargeable Battery | | |
| Additional Included Accessories | Armrest with Strap USB-C Magnetic Charging Cable Getting Started Guide | Armrest with Strap Wired Headphones USB-C Magnetic Charging Cable Getting Started Guide | |
| Waterproof | Fully Waterproof up to 5 m (16 ft) | | |
| Operating Temperature Range | -10°C to +40°C (+14°F to +104°F) | | |
| Storage Temperature Range | -20°C to +70°C (-4°F to +158°F) | | |
| Key Technologies | Multi-IQ® | Multi-IQ, Low-Latency Bluetooth® LE Audio | |



What's Included



V12X™
12" x 9" Double-D Coil with Skid Plate
560 and 560 PRO-PACK



V10X™
10" x 7" Double-D Coil with Skid Plate
360 and 460



VBX™
8" x 5" Double-D Coil with Skid Plate
560 PRO-PACK



Armrest with Strap
ALL



USB-C Magnetic Charging Cable
ALL



Wired Headphones
460 and 560



ML60 Bluetooth® LE Audio Wireless Earbuds
560 PRO-PACK



Getting Started Guide and Compliance Guide
ALL

VANQUISH 560 PRO-PACK is based on the standard VANQUISH 560 with the following differences: Includes ML60 low-latency Bluetooth® LE audio wireless earbuds and the VBX 8" x 5" Double-D coil with a skid plate. Excludes wired 3.5 mm (1/8") headphones.

Bluetooth® LE Audio with LC3 codec delivers faster sound for a more immersive detecting experience. Incompatible with standard Bluetooth devices.

Equipment may vary according to the model or items ordered with your detector. Minelab reserves the right to respond to ongoing technical progress by introducing changes in design, equipment and technical features at any time. For the most up-to-date specifications for your VANQUISH detector visit: www.minelab.com



www.minelab.com

MINELAB®, VANQUISH®, Multi-IQ®, VBX™, V10X™, and V12X™ are trademarks of Minelab Electronics Pty. Ltd. Images and graphics on this document are for illustration purposes only. Product configuration may vary from the configuration shown. Please refer to the manual for detailed operational guidance.

4907-1073-EN-1